

日期/Date

档案员  
Filing Clerk

1




2

3

4

5

6



## 技术参数:

## 插芯:

- 插针数: 3/4
- 额定电流:
  - 电力区: 40A
  - 信号区: 10A
- 额定电压: 830V
- 额定脉冲电压: 8kV
- 污染等级: 3
- 依据UL的额定电压: 600V
- 绝缘阻抗:  $> 10^{10}\Omega$
- 材料: 聚碳酸酯
- 颜色: RAL 7032 (浅灰色)
- 温度范围:  $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
- 依据UL 94的阻燃等级: V0
- 可插拔次数:  $> 500$
- 插针:
  - 接线方式: 冷压连接
  - 材料: 铜合金
  - 表面处理:
    - 镀银
    - 镀金
  - 接触电阻:
    - 电力区:  $< 1\text{m}\Omega$
    - 信号区:  $< 3\text{m}\Omega$
  - 线径范围:
    - 电力区:  $1.5-6\text{mm}^2(16-10\text{ AWG})$
    - 信号区:  $0.14-2.5\text{mm}^2(26-14\text{ AWG})$
  - 最大电缆直径: 5mm
  - 工具:
    - 冷压钳:
      - TL02-0G( $1.5-6\text{mm}^2$ )
      - TL02-3G( $4/6/10\text{mm}^2$ )
      - TL02G( $0.14-4\text{mm}^2$ )
    - 退针器:
      - TL06G(40A冷压针)
      - TL00(10A冷压针 $\text{mm}^2$ )

## Technical specification:

## Inserts:

- No. of contact: 3/4
- Rated current:
  - Power contacts: 40A
  - Signal contacts: 10A
- Rated voltage: 830V
- Rated impulse voltage: 8kV
- Pollution degree: 3
- Rated voltage acc.to UL: 600V
- Insulation resistance:  $> 10^{10}\Omega$
- Material: polycarbonate
- Colour: RAL 7032(light grey)
- Temperature range:  $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
- Flammability acc.to UL 94: V0
- Mating cycles:  $> 500$
- Contacts:
  - Terminal: crimp terminal
  - Material: copper alloy
  - Surface:
    - hard-silver plated
    - hard-gold plated
  - Contact resistance:
    - Power contacts:  $< 1\text{m}\Omega$
    - Signal contacts:  $< 3\text{m}\Omega$
  - Wire gauge:
    - Power contacts:  $1.5-6\text{mm}^2(16-10\text{ AWG})$
    - Signal contacts:  $0.14-2.5\text{mm}^2(26-14\text{ AWG})$
  - Tools:
    - Crimp contact tool:
      - TL02-0G( $1.5-6\text{mm}^2$ )
      - TL02-3G( $4/6/10\text{mm}^2$ )
      - TL02G( $0.14-4\text{mm}^2$ )
    - Contact removal tool:
      - TL06G(for crimp contacts 40A)
      - TL00(for crimp contacts 10A)

						表面处理 Finish	-		图号 Drawing No.	-	
						材料 Material	-		产品代号 Part Code	HME-006-FC	
标记 Mark	处数 Number	变更描述/Description		签名 Signature	日期 Date				产品料号 Part No.	1290070200001	
	姓名/Name	日期/Date		姓名/Name	日期/Date	比例 Scale	版本 REV.	重量 Weight	数量 Qty.	产品名称 Part Name	-
绘图 Drawn	BQ LUO	18.10.2010	标准化 Stand.	-	-	1:1	V1.0	9.4g	-		
审核 Checked	P RAO	18.10.2010									
工艺 Process	-	-	批准 Approved	YY LIN	18.10.2010			All Dimensions in mm Original Size DIN A 4		厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD	

1

2

3

4

5

6