


技术参数:

- 产品系列: M12 A-code
- 插针数: 3
- 额定电流(40°C): 4 A
- 额定电压: 250 V
- 脉冲电压: 2500 V
- 污染等级: 3
- 接触电阻: $\leq 10 \text{ m}\Omega$
- 绝缘电阻: $\geq 100 \text{ M}\Omega$
- 锁紧方式: 螺纹M12X1
- 电缆类型: PUR, 黑色RAL9005
- 线规: 0.34 mm^2 (AWG22)
- 防护等级: IP67
- 插拔次数: > 100
- 使用温度范围: $-25^\circ\text{C} - +85^\circ\text{C}$
- 锁紧螺帽: 不锈钢
- 外壳材料: TPU
- 插体材料: PA
- 插针材料: 铜合金
- 插针电镀材料: 金

Technical specification:


- Series: M12 A-code
- Number of contacts: 3
- Rated current(40°C): 4 A
- Rated voltage: 250 V
- Rated impulse voltage: 2500 V
- Pollution degree: 3
- Contact resistance: $\leq 10 \text{ m}\Omega$
- Insulation resistance: $\geq 100 \text{ M}\Omega$
- Connectoe locking system: Screw M12x1
- Cable type: PUR , Black RAL 9005
- Wire gauge: 0.34 mm^2 (AWG22)
- Degree of protection: IP67
- Mating cycles: > 100
- Temperature range: $-25^\circ\text{C} - +85^\circ\text{C}$
- Material of locking system: Stainless steel
- Material of housing: TPU
- Material of Insert: PA
- Material of contact: copper alloy
- Contact plating: Au



剥线长度
 Stripping length of the sheath

例如型号“M12S-M03A-S-L-PUR”,
 “L”表示带线长度, 单位m.

Ex: Part code “M12S-M03A-S-L-PUR”,the
 “L” represents the cable length, unit m.



						表面处理 Finish	-				图号 Drawing No.	-
						材料 Material	-				产品代号 Part Code	M12S-M03A-S-5.0-PUR
标记 Mark	处数 Number	变更描述/Description			签名 Signature	日期 Date	比例 Scale	版本 REV.	重量 Weight	数量 Qty.	产品料号 Part No.	1630035014242
绘图 Drawn	CH CHEN	姓名/Name	日期/Date	标准化 Stand.	-	1:1	V1.0	183.9g	-	产品名称 Part Name	-	
审核 Checked	ZM LIN	姓名/Name	日期/Date									
工艺 Process	-	批准 Approved	YY LUO	日期/Date	12.01.2017	All Dimensions in mm Original Size DIN A 4				厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD		