



技术参数:

- 材料: 压铸铝
- 表面处理: 粉末喷涂
- 颜色: RAL 9005 (黑色)
- 温度范围: -40℃ - +125℃
- 防护等级: IP68/IP69K
- 出线方向: 侧出线
- 出线孔数: 1
- 螺纹规格: M20
- 密封元件: NBR

Technical specification:

- Material: aluminium die-cast
- Surface: powder-coated
- Colour: RAL 9005(black)
- Temperature range: -40℃ - +125℃
- Degree of protection: IP68/IP69K
- Cable entry: side entry
- No. of cable entries: 1
- Thread size: M20
- Hoods/Housings sealing: NBR

| | | | | | | | | | | | | |
|---------------|--------------|------------------|---------|----------------|-----------------|----------------|-------------|------------|---|---|-------------------|---------------|
| | | | | | | 表面处理 Finish | - | | | 图号 Drawing No. | - | |
| | | | | | | 材料 Material | - | | | 产品代号 Part Code | HP6B/H-SFH-2H-M20 | |
| 标记 Mark | 处数 Number | 变更描述/Description | | | 签名 Signature | 日期 Date | 比例 Scale | 版本 REV. | 重量 Weight | 数量 Qty. | 产品料号 Part No. | 1136062205002 |
| 绘图 Drawn | BQ LUO | 姓名/Name | 日期/Date | 标准化 Stand. | - | - | 5:2 | V1.0 | 940g | - | 产品名称 Part Name | - |
| 审核 Checked | P RAO | 姓名/Name | 日期/Date | | | | | | | | | |
| 工艺 Process | - | 姓名/Name | 日期/Date | 批准 Approved | YY LIN | 18.10.2010 | | | All Dimensions in mm Original Size DIN A 4 | | | |
| | | | | | | | | | | 厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO., LTD. | | |