


日期/Date	档案员 Filing Clerk	线径/Wire Gauge		d	剥线长度 Stripping Length	重量/Weight g
		mm ²	AWG			
CSSM-0.25	1010141100101	0.09-0.25	28-24	0.64	5	0.19
CSSM-0.33	1010141100201	0.25-0.33	26-22	0.9	5	0.18
CSSM-0.52	1010141100501	0.33-0.52	22-20	1.12	5	0.17




技术参数:


- 材料: 铜合金
- 表面处理: 镀银
- 额定电流: 5A
- 接触电阻: $\leq 3m\Omega$
- 线径范围: 0.09-0.52mm²(28-20 AWG)
- 可插拔次数: ≥ 500

Technical specification:

- Material: copper alloy
- Surface: silver plated
- Rated current: 5A
- Contact resistance: $\leq 3m\Omega$
- Wire gauge: 0.09-0.52mm²(28-20 AWG)
- Mating cycles: ≥ 500



标记 Mark	处数 Number	变更描述/Description		姓名/Name	日期/Date	表面处理 Finish	图号 Drawing No.				
						-	-				
						材料 Material	-				
						比例 Scale	版本 REV.	重量 Weight	数量 Qty.	产品代号 Part Code	CSSM-XX
绘图 Drawn	BQ LUO	18.10.2010	标准化 Stand.	-	-	4:1	V1.0	-	-	产品料号 Part No.	-
审核 Checked	P RAO	18.10.2010								产品名称 Part Name	-
工艺 Process	-	-	批准 Approved	YY LIN	18.10.2010					厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD	



All Dimensions in mm
Original Size DIN A 4