



- 技术参数:
- 材料: 铜合金
 - 表面处理: 镀银
 - 额定电流: 650A
 - 接触电阻: $\leq 0.3m\Omega$
 - 线径范围: 185/240mm²
 - 最大电缆直径: 27/32mm
 - 可插拔次数: ≥ 500
 - 压力要求: 130kN

- Technical specification:
- Material: copper alloy
 - Surface: hard-silver plated
 - Rated current: 650A
 - Contact resistance: $\leq 0.3m\Omega$
 - Wire gauge: 185/240mm²
 - Max. insulation diameter: 27/32mm
 - Mating cycles: ≥ 500
 - Pressing force requirement: 130kN

产品名称/Part Name	产品料号/Part No.	D1
CHSM650-185	1010301102301	25.5
CHSM650-240	1010301102401	29

						表面处理 Finish		-		图号 Drawing No.		-	
						材料 Material		-		产品代号 Part Code		CHSM650-XX	
标记 Mark	处数 Number	变更描述/Descriptions		签名 Signature		日期 Date				产品料号 Part No.		-	
	姓名/Name	日期/Date		姓名/Name	日期/Date	比例 Scale	版本 REV.	重量 Weight	数量 Qty.	产品名称 Part Name		-	
绘图 Drawn	SX. HUANG	19.11.20	标准化 Stand.			1:1	V1.0	-	1				
审核 Checked	HZ. LAN	19.11.20											
工艺 Process				批准 Approved	HQ. ZHANG	19.11.20			All Dimensions in mm Original Size DIN A4		厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD		