


技术参数:

- 额定电流: 6A
- 温度范围: -55℃ - +125℃
- 可插拔次数: >400
- 接线方式: 冷压
- 接触电阻: <15mΩ
- 材料: 铜合金
- 表面处理: 局部镀金
- 线径范围: 0.5-1.5mm<sup>2</sup>/20-16 AWG

Technical specification:

- Rated current: 6A
- Temperature range: -55℃ - +125℃
- Mating cycles: ≥400
- Terminal: crimp terminal
- Contact resistance: ≤15mΩ
- Material: copper alloy
- Surface: selective gold plating
- Wire gauge: 0.5-1.5mm<sup>2</sup>/20-16 AWG



					表面处理 Finish	-			图号 Drawing No.	-
					材料 Material	-			产品代号 Part Code	CBGF-1.5P
标记 Mark	处数 Number	变更描述/Description		签名 Signature	日期 Date				产品料号 Part No.	1010402020901
	姓名/Name	日期/Date		姓名/Name	日期/Date	比例 Scale	版本 REV.	重量 Weight	数量 Qty.	产品名称 Part Name
绘图 Drawn	TC YE	10.11.2021	标准化 Stand.	-	-	2:1	V1.1	0.35g	-	-
审核 Checked	HZ LAN	10.11.2021								
工艺 Process	-	-	批准 Approved	HQ ZHANG	10.11.2021	All Dimensions in mm Original Size DIN A 4			厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD	